

Safety Data Sheet

DAUBERT
CHEMICAL COMPANY, INC.

Stock Number: 3115033
Revision Date: 11-28-2018
Replaces: 10-24-2016

TECTYL® 502C, CLASS II

1. Identification

Product identifier used on the label: TECTYL® 502C, CLASS II
Stock Number: 3115033

Other means of identification:
Synonyms: None
Chemical family: Mixture

Recommended use of the chemical and restrictions on use:
Recommended use: Corrosion Preventive Compound
Restrictions on use: Uses other than those described above

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party: Daubert Chemical Company
4700 S. Central Avenue
Chicago, IL 60638

Telephone number: 708-496-7350
E-mail address: SDS@Daubert.com
Emergency phone number: Chemtrec: (800) 424-9300

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard
Symbols:



GHS Classification: Skin Corrosion/Irritation Category 2; Flammable Liquid Category 3; Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3; Hazardous to the aquatic environment - Acute Category 3; Hazardous to the aquatic environment - Chronic Category 3

Signal Word: Warning

Hazard Statements: Flammable liquid and vapor
Causes skin irritation
May cause respiratory irritation
May cause drowsiness or dizziness
Harmful to aquatic life
Harmful to aquatic life with long lasting effects

Safety Data Sheet

Product identifier used on the label: TECTYL® 502C, CLASS II

Stock Number: 3115033

Revision Date: 11-28-2018

Replaces: 10-24-2016

Unclassified Hazards (HNOC)::

None Identified

Precautionary Statements:

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/ vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Response:

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment: see Section 4 on SDS.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use appropriate media to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/container to a suitable disposal site in accordance with local/national/international regulations.

Hazards not otherwise classified:

No data available

Safety Data Sheet

Product identifier used on the label: TECTYL® 502C, CLASS II

Stock Number: 3115033

Revision Date: 11-28-2018

Replaces: 10-24-2016

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS #	%
Petrolatum (petroleum), oxidized, zinc salt	None	68918-69-4	30 - 60
Hydrotreated light distillate (Petroleum)	None	64742-47-8	30 - 60

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

- Inhalation:** If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.
- Eye Contact:** Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
- Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
- Ingestion:** Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration into lungs.

Most important symptoms/effects, acute and delayed: Causes skin irritation. May cause respiratory irritation May cause drowsiness or dizziness

Indication of immediate medical attention and special treatment needed, if necessary: Consult a physician. Treat symptomatically.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

- Suitable extinguishing media:** Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire.

Safety Data Sheet

Product identifier used on the label: TECTYL® 502C, CLASS II

Stock Number: 3115033

Revision Date: 11-28-2018

Replaces: 10-24-2016

Unsuitable extinguishing media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.

Hazardous combustion products:

Carbon dioxide, Carbon monoxide, Hydrocarbons, Sulfur compounds

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up:

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

7. Handling and storage

Precautions for safe handling:

Avoid contacting and avoid breathing the material. Use only in a well ventilated area. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

Safety Data Sheet

Product identifier used on the label: TECTYL® 502C, CLASS II

Stock Number: 3115033

Revision Date: 11-28-2018

Replaces: 10-24-2016

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Do not store in direct sunlight. Keep away from heat, sparks, and flame.

Materials to Avoid/Chemical Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Hydrotreated light distillate (Petroleum)		200 mg/m ³	No data available	No data available

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

Respiratory Protection:

Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator.

Respirator Type(s):

NIOSH approved air purifying respirator with organic vapor/acid gas cartridge., NIOSH approved air purifying respirator with organic vapor cartridge.

Eye protection:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Safety Data Sheet

Product identifier used on the label: TECTYL® 502C, CLASS II

Stock Number: 3115033

Revision Date: 11-28-2018

Replaces: 10-24-2016

Skin protection:	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
Gloves:	Chemically resistant gloves
Other protective equipment:	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
General hygiene conditions:	Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state:	Liquid
Color:	Amber
Odor:	Solvent Odor Slight
Odor Threshold:	No data available
pH:	No data available
Melting point/freezing point (°C):	
Melting Point (°C):	No data available
Freezing point (°C):	No data available
Initial boiling point and boiling range (°C):	No data available
Flash Point:	>= 105 °F(41 °C)
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available

Safety Data Sheet

Product identifier used on the label: TECTYL® 502C, CLASS II

Stock Number: 3115033

Revision Date: 11-28-2018

Replaces: 10-24-2016

Upper/lower flammability or explosive limits:

Upper flammability or explosive limits:	No data available
Lower flammability or explosive limits:	No data available
Vapor pressure:	2 mmHg @ 20°C
Vapor density:	>1 (Air=1)
Relative density:	0.87
Solubility(ies):	Negligible; 0-1%
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature (°C):	No data available
Decomposition Temperature (°C):	No data available
Viscosity:	Typical 200 cSt @ 40°C
Volatiles, % by weight:	33
VOC, Material, lb/gal	2.4
VOC, Material, grams/liter	287.9
VOC minus exempt solvents & water, g/l	287.9

10. Stability and reactivity

Reactivity:	Not expected to be reactive
Chemical stability:	Hazardous polymerization will not occur.
Possibility of hazardous reactions:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid (e.g., static discharge, shock, or vibration):	Temperatures above flash point in combination with sparks, open flames, or other sources of ignition. Elevated temperatures. Contamination.
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	Under normal conditions of use & storage, decomposition and hazardous decomposition products are unlikely.

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):	Eye contact, Inhalation, Skin contact
---	---------------------------------------

Safety Data Sheet

Product identifier used on the label: TECTYL® 502C, CLASS II

Stock Number: 3115033

Revision Date: 11-28-2018

Replaces: 10-24-2016

Symptoms related to the physical, chemical and toxicological characteristics:

Causes skin irritation. . May cause respiratory irritation. May cause drowsiness or dizziness

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity:

Harmful if swallowed. Estimated to be 2.0 - 5.0 g/kg; slightly toxic

Skin Contact:

Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Inhalation Toxicity:

May cause respiratory irritation

Eye Contact:

Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

Sensitization:

None known

Mutagenicity:

No data

Reproductive and Developmental Toxicity:

No data available

Carcinogenicity:

There are no carcinogenic ingredients present at or over 0.1%.

STOT-single exposure:

Classification has been based on toxicological information of the components in Section 3.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petrolatum (petroleum), oxidized, zinc salt	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	
Hydrotreated light distillate (Petroleum)	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 20 mg/L

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen.			

Safety Data Sheet

Product identifier used on the label: TECTYL® 502C, CLASS II

Stock Number: 3115033

Revision Date: 11-28-2018

Replaces: 10-24-2016

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available): No data available

Ecological Toxicity Data:

Chemical Name	CAS #	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Petrolatum (petroleum), oxidized, zinc salt	68918-69-4	No data available	No data available	LC50(96 HR) FISH = 10 - 100 mg/L

Persistence and degradability: No data

Bioaccumulative potential: No data available

Mobility in soil: No data available

Other adverse effects (such as hazardous to the ozone layer): No data available

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging: Spent or discarded material may be a hazardous waste. Dispose of by incineration following Federal, State, Local, or Provincial regulations.

Waste codes / waste designations: D001

14. Transport information

Domestic Ground in containers <= 119 GL Corrosion preventive/Non-Regulated

Domestic Ground in containers > 119 GL UN1268, PETROLEUM DISTILLATES, N.O.S.,(Naphtha Solvent), Combustible liquid, PG III

Shipping name for Export, Air (IATA) UN1268, PETROLEUM DISTILLATES, N.O.S.,(Naphtha Solvent),3, PG III

Shipping name for Export, Sea (IMDG) UN1268, PETROLEUM DISTILLATES, N.O.S.,(Naphtha Solvent),3, PG III

Safety Data Sheet

Product identifier used on the label: TECTYL® 502C, CLASS II

Stock Number: 3115033

Revision Date: 11-28-2018

Replaces: 10-24-2016

Marine Pollutant?

No

15. Regulatory information

Status of formula components on selected national regulatory inventories:

LIST	STATUS
TSCA	All components in this product are on the TSCA Inventory or exempt.
Canadian DSL	One or more chemical substances in this material are on the Canadian NDSL and the remainder are included on the Canadian DSL or are exempt.

Chemical Name	CAS #	Regulation	Percent
Cumene	98-82-8	Prop. 65 - Cancer	TRACE
Naphthalene	91-20-3	Prop. 65 - Cancer	TRACE
Benzene	71-43-2	Prop. 65 - Cancer	TRACE
Ethylbenzene	100-41-4	Prop. 65 - Cancer	TRACE
Toluene	108-88-3	Prop. 65 - Developmental and/or Reproductive	<0.1
Benzene	71-43-2	Prop. 65 - Developmental and/or Reproductive	TRACE
No CERCLA-listed chemicals in this product.		CERCLA	
No 313-listed chemicals in this product.		SARA 313	
No SARA 302 EHS-listed chemicals in this product.		SARA EHS	

Safety Data Sheet

Product identifier used on the label: TECTYL® 502C, CLASS II

Stock Number: 3115033

Revision Date: 11-28-2018

Replaces: 10-24-2016

16. Other information, including date of preparation or last revision.

SDS Prepared by: DAUBERT\HALINSKI

Revision Date: 11-28-2018

Revision Number: 23

Reason for revision: Reviewed
Approved: M. Longo

Disclaimer: Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.