

Safety Data Sheet

Revision Date 11-21-2016
Revision Number 14



SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier	3116 TECTYL® 506EH
Details of the supplier of the safety data sheet	Daubert Chemical Company 4700 S. Central Avenue Chicago, IL 60638 708-496-7350
Emergency telephone number	Chemtrec: (800) 424-9300
Relevant identified uses of the substance or mixture and uses advised against	Corrosion Preventive Compound

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification	Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2B Flammable Liquid Category 3 Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3
Signal Word	Warning
Hazard Statements	Flammable liquid and vapor Causes skin and eye irritation May cause respiratory irritation May cause drowsiness or dizziness
Unclassified Hazards (HNOC):	None Identified
Precautionary Statements	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet

Revision Date 11-21-2016
Revision Number 14

Response	IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment: None known If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.
Storage	Use dry chemical, water fog, CO2, foam or sand/earth for extinction. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

SECTION 3 Composition/information on ingredients

Chemical Name	CAS #	%
Hydrotreated light distillate (Petroleum)	64742-47-8	30 - 50

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 First aid measures

Inhalation	If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.
Eyes	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact	Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration into lungs.
Most important symptoms/effects, acute and delayed	See Section 11
Indication of immediate medical attention and special treatment needed	Treat symptomatically.

SECTION 5 Firefighting measures

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Safety Data Sheet

Revision Date 11-21-2016
Revision Number 14

Fire and/or Explosion Hazards	Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.
Fire Fighting Methods and Protection	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.
Hazardous Combustion Products	Carbon dioxide, Carbon monoxide, Hydrocarbons, Sulfur compounds

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods and materials for containment and cleaning up	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Collect and discard in accordance with local, state and national regulations.

SECTION 7 Handling and storage

Precautions for safe handling	Mildly irritating material. Avoid unnecessary exposure. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.
Conditions for safe storage, including any incompatibilities	Store in a cool dry place. Isolate from incompatible materials. Keep container closed when not in use. Keep away from heat, sparks, and flame.
Incompatible materials	Strong oxidizing agents

SECTION 8 Exposure controls/personal protection

Control parameters

<u>Chemical Name</u>	<u>ACGIH TLV</u>	<u>ACGIH STEL</u>	<u>OSHA PEL</u>
Hydrotreated light distillate (Petroleum)	200 mg/m ³		

Safety Data Sheet

Revision Date 11-21-2016
Revision Number 14

Engineering Measures	Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits
Respiratory Protection	Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator.
Eye Protection	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.
Skin Protection	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
Gloves	Chemically resistant gloves

SECTION 9 Physical and chemical properties (Typical, not specification)

Physical State	Liquid
Color	Amber
Odor	Slight Solvent Odor
Odor Threshold	No data available
pH	No data available
Melting Point/freezing point, °C	No data available
Initial boiling point and boiling range, °C	No data available
Flash Point	105 °F(41 °C)
Evaporation Rate	No data available
Flammability (Solid, Gas)	No data available
Lower Flammable/Explosive Limit, % in air	No data available
Upper Flammable/Explosive Limit, % in air	No data available
Vapor Pressure	2 mmHg
Vapor Density	>1 (Air=1)
Specific Gravity @ 25°C	0.87
Solubility in Water	Negligible; 0-1%
Octanol/Water Partition Coefficient	No data available
Autoignition Temperature	No data available
Decomposition Temperature	No data available
Viscosity	140 cSt @ 40°C
Volatiles, % by weight	39
VOC, Material, lb/gal	2.83
VOC, Material, grams/liter	339.5

SECTION 10 Stability and reactivity

Reactivity	No data available
Chemical stability	Stable under normal conditions. Hazardous polymerization will not occur.

Safety Data Sheet

Revision Date 11-21-2016
Revision Number 14

Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Contamination. Elevated temperatures.
Incompatible materials	Strong oxidizing agents
Hazardous decomposition products	Under normal conditions of use & storage, decomposition and hazardous decomposition products are unlikely.

SECTION 11 Toxicological information

Likely Routes of Entry	Inhalation, Skin contact, Eye contact
Target Organs Potentially Affected by Exposure	Central Nervous System, Respiratory Tract, Skin, Eyes, Kidneys, Liver, Nervous System
Chemical Interactions That Change Toxicity	No chemical interaction known to affect toxicity.
Medical Conditions Aggravated	Skin contact may aggravate existing skin disease, Respiratory disease including asthma and bronchitis

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Other possible symptoms include; wheezing and coughing due to pulmonary edema (fluid build-up in lungs).
Skin Contact	Can cause minor skin irritation, defatting, and dermatitis.
Eye Contact	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
Ingestion Toxicity	Harmful if swallowed.

Long-Term (Chronic) Health Effects

Carcinogenicity	There are no carcinogenic ingredients present at or over 0.1%.
Inhalation	Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.
Skin Contact	Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.
Ingestion	Under normal industrial usage conditions, ingestion is highly unlikely.

Component Toxicology Data

Chemical Name	CAS Number	LD50/LC50
Hydrotreated light distillate (Petroleum)	64742-47-8	Dermal LD50 Rabbit > 2000 mg/kg Oral LD50 Rat > 5000 mg/kg Inhalation LC50 (4h) Rat > 20 mg/L

SECTION 12 Ecological information

Overview	No ecological information available
Mobility	No data
Persistence	No data
Bioaccumulation	No data
Degradability	No data

Ecotoxicity Data

Chemical Name	CAS Number	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available				

Safety Data Sheet

Revision Date 11-21-2016
Revision Number 14

SECTION 13 Disposal considerations

Waste Description for Spent Product Spent or discarded material may be a hazardous waste.
Disposal Methods Dispose of by incineration following Federal, State, Local, or Provincial regulations.
Waste Disposal Code(s) D001

SECTION 14 Transport information

Full shipping name for Export, Air, Sea (any quantity unless flash pt. >150°F) or vessels of 119 GL or more UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG III,
Domestic Ground in vessels < 119 gal. Non-Regulated

SECTION 15 Regulatory information

Status of formula components on selected national regulatory inventories:

LIST	STATUS
TSCA	All components in this product are on the TSCA Inventory or exempt.
Canadian DSL	All chemical substances in this material are included on or exempted from listing on the Canadian DSL.

Chemical Name	CAS #	Regulation	Percent
No CERCLA-listed chemicals in this product.		CERCLA	
No 313-listed chemicals in this product.		SARA 313	
No SARA 302 EHS-listed chemicals in this product.		SARA EHS	

SECTION 16 Other information

Revision 11-21-2016
Date
Disclaimer Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.
Version Reviewed
Comments Approved: M. Duncan