

Stock Number: 3123000 **Revision Date:** 10-06-2017 **Replaces:** 05-23-2017

TECTYL® 517

1. Identification

Product identifier used on the label: TECTYL® 517
Stock Number: 3123000

Other means of identification:

Synonyms: None

Recommended use of the chemical and restrictions on use:

Recommended use: Corrosion Preventive Compound

Restrictions on use: Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

Daubert Chemical Company

importer, or other responsible party:

4700 S. Central Avenue

Chicago, IL 60638

Telephone number:

E-mail address:

708-496-7350

Emergency phone number: Chemtrec: (800) 424-9300

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:





GHS Classification: Skin Corrosion/Irritation Category 2; Serious Eye Damage/Eye Irritation

Category 2B; Flammable Liquid Category 3; Specific Target Organ

Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word: Warning

Hazard Statements: Flammable liquid and vapor

Causes skin and eye irritation

May cause respiratory irritation

May cause drowsiness or dizziness

Unclassified Hazards (HNOC):: None Identified

Precautionary Statements:

Prevention: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Product identifier used on the label: TECTYL® 517

Stock Number: 3123000 Revision Date: 10-06-2017 Replaces: 05-23-2017

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face

protection.

Response: If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for

breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use appropriate media to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal: Dispose of contents/container to a suitable disposal site in accordance

with local/national/international regulations.

Hazards not otherwise classified: No data available

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%
Hydrotreated light distillate (Petroleum)	None	64742-47-8	30 - 50

Product identifier used on the label: TECTYL® 517

Stock Number: 3123000 Revision Date: 10-06-2017 Replaces: 05-23-2017

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: If symptoms are experienced remove source of contamination or move

victim to fresh air and obtain medical advice.

Eye Contact: Flush eyes with plenty of water for at least 20 minutes retracting eyelids

often. Tilt the head to prevent chemical from transferring to the

uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder.

Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Provide

medical care provider with this SDS. If vomiting occurs, lean victim

forward to reduce risk of aspiration into lungs.

Most important symptoms/effects,

acute and delayed:

Causes skin and eye irritation May cause respiratory irritation May cause

drowsiness or dizziness

Indication of immediate medical attention and special treatment

needed, if necessary:

Consult a physician. Treat symptomatically.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray

when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the

chemical:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may

lead to injury or death.

Product identifier used on the label: TECTYL® 517

Stock Number: 3123000 Revision Date: 10-06-2017 Replaces: 05-23-2017

Hazardous combustion products:

Carbon dioxide, Carbon monoxide, Hydrocarbons

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up:

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

7. Handling and storage

Precautions for safe handling:

Avoid contacting and avoid breathing the material. Use only in a well ventilated area. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store in a cool dry place. Isolate from incompatible materials. Do not store in direct sunlight Keep away from heat, sparks, and flame. Keep container closed when not in use.

Materials to Avoid/Chemical Incompatibility:

Strong oxidizing agents

Product identifier used on the label: TECTYL® 517

Stock Number: 3123000 Revision Date: 10-06-2017 Replaces: 05-23-2017

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Hydrotreated light		200 mg/m3	No data available	No data available
distillate (Petroleum)				

Appropriate engineering controls: Local exhaust ventilation or other engineering controls are normally

required when handling or using this product to avoid overexposure.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

Engineering controls must be designed to meet the OSHA chemical

specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Proper ventilation (at a minimum) will be required when handling this

product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the

use of a respirator.

Eye protection: Wear chemically resistant safety glasses with side shields when handling this

product. Do not wear contact lenses.

Skin protection: Wear protective gloves. Inspect gloves for chemical break-through and

replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

Gloves: Chemically resistant gloves

Other protective equipment: Wear protective gloves. Inspect gloves for chemical break-through and

replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

Product identifier used on the label: TECTYL® 517

Stock Number: 3123000 Revision Date: 10-06-2017 Replaces: 05-23-2017

General hygiene conditions:

Do not use pressure to empty container. Use spark-proof tools and explosion-proof equipment. Guard against dust accumulation of this material. Keep in air-tight containers- material is hygroscopic. Minimize dust generation and accumulation. Use with adequate ventilation "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid
Color: Black

Odor: Solvent Odor

Slight

Odor Threshold: No data available pH: No data available

Melting point/freezing point:

Melting Point:No data availableFreezing point:No data availableInitial boiling point and boiling range (°C):No data availableFlash Point:>= 105 °F(41 °C)Evaporation Rate:No data availableFlammability (solid, gas):No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive limits:No data available **Lower flammability or explosive limits:**No data available

Vapor pressure:2 mmHgVapor density:>1 (Air=1)Relative density:0.945

Solubility(ies):Negligible; 0-1%Partition coefficient: n-octanol/water:No data availableAuto-ignition temperature (°C):No data available

Product identifier used on the label: TECTYL® 517

Stock Number: 3123000 Revision Date: 10-06-2017 Replaces: 05-23-2017

Decomposition Temperature:No data available

Viscosity: 3000 cP

Volatiles, % by weight: 46
VOC, Material, lb/gal 3.74

VOC, Material, grams/liter 448.6

VOC minus exempt solvents & water, g/l 449

10. Stability and reactivity

Reactivity: Not expected to be reactive

Chemical stability: Hazardous polymerization will not occur.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not

occur.

Conditions to avoid (e.g., static

discharge, shock, or vibration):

Temperatures above flash point in combination with sparks, open flames,

or other sources of ignition. Elevated temperatures. Contamination.

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Under normal conditions of use & storage, decomposition and hazardous

decomposition products are unlikely.

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Eye contact, Skin contact, Inhalation

Symptoms related to the physical,

chemical and toxicological

characteristics:

Causes skin and eye irritation. May cause respiratory irritation. May

cause drowsiness or dizziness

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity: Harmful if swallowed. Estimated to be > 5.0 g/kg; practically non-toxic

Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to

cause permanent damage.

Inhalation Toxicity: May cause respiratory irritation

Product identifier used on the label: TECTYL® 517

Stock Number: 3123000 Revision Date: 10-06-2017 Replaces: 05-23-2017

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to

permanently injure eye tissue.

Sensitization: None known

Mutagenicity: No data

Reproductive and DevelopmentalNo data available

Toxicity:

Carcinogenicity:

There are no carcinogenic ingredients present at or over 0.1%.

STOT-single exposure: Classification has been based on toxicological information of the

components in Section 3.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hydrotreated light	Oral LD50 Rat > 5000	Dermal LD50 Rabbit > 2000	Inhalation LC50 (4h) Rat >
distillate (Petroleum)	mg/kg	mg/kg	20 mg/L

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer			

12. Ecological information

Ecotoxicity (aquatic and terrestrial,

No data available

where available):

Ecological Toxicity Data:

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available				

Persistence and degradability: No data

Bioaccumulative potential: No data available

Mobility in soil: No data available

Product identifier used on the label: TECTYL® 517

Stock Number: 3123000 **Revision Date: 10-06-2017** Replaces: 05-23-2017

Other adverse effects (such as hazardous to the ozone layer): No data available

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the

disposal of any contaminated

packaging:

Spent or discarded material may be a hazardous waste.

Dispose of by incineration following Federal, State, Local, or Provincial

regulations.

Waste codes / waste designations: D001

14. Transport information

Domestic Ground in containers <= 119 GL Corrosion preventive, Non-Regulated

Domestic Ground in containers > 119 GL UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent),

Combustible liquid, PG III

UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG Shipping name for Export, Air (IATA)

Shipping name for Export, Sea (IMDG) UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG

Ш

Marine Pollutant? No

15. Regulatory information

Status of formula components on selected national regulatory inventories:

LIST	STATUS
TSCA	All components in this product are on the TSCA Inventory or exempt.
Canadian DSL	All chemical substances in this material are included on or exempted from listing on the Canadian DSL.

Product identifier used on the label: TECTYL® 517

Stock Number: 3123000 Revision Date: 10-06-2017 Replaces: 05-23-2017

Chemical Name	CAS#	Regulation	Percent
Carbon black (airborne, unbound particles of respirable size)	1333-86-4	California Prop 65	0.1 - 1
No CERCLA-listed chemicals in this product.		CERCLA	
No 313-listed chemicals in this product.		SARA 313	
No SARA 302 EHS-listed chemicals in this product.		SARA EHS	

16. Other information, including date of preparation or last revision.

SDS Prepared by: DAUBERT\HALINSKI

Revision Date: 10-06-2017

Revision Number: 16

Reason for revision: Reviewed

Approved: M. Longo

Disclaimer: Although the information contained herein is believed to be reliable, it is

furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and

storage.